

# Technical Datasheet



## MCU200: Controller and Sensors

### Suspended solids detection

Model: MCU200 series

#### Key Features

- Ultrasonic technology
- Level or interface detection
- Oil in Water or Water in Oil detection
- Choice of sensors for tanks or pipes
- LED indication for Normal, Alarm and Fault
- DPDT relay output, configurable for wet to dry, or dry to wet changeover
- Cable check fault detection
- Selectable time delay
- Unaffected by liquid colour/opacity, or conductivity
- Wall mounting IP65 polycarbonate enclosure

#### Product Overview

Ultrasonic point level switches may be used in industrial processes to detect high or low liquid levels or liquid interfaces, such as a sludge blanket. They can also discriminate between liquid and air, or immiscible liquids such as oil and water. They are therefore commonly used in settlement tanks and for oil or water contamination in marine and other industries.

Other products in the series include:

- MSM400 for continuous sludge density measurement with 4-20mA, HART and relay outputs
- DMSP ultrasonic level transmitters



#### Product applications

- Sludge level detection
- Settlement tank high level alarm
- Water in oil / oil in water detection
- Liquid level detection
- For use in tanks or pipes

#### How can we help you?

Delta Mobrey offers fast, efficient and knowledgeable support when and where you need it. Please visit our website at [www.delta-mobrey.com](http://www.delta-mobrey.com) to find your local support centre or call us on:

**+44 (0)1252 729140**

Suspended Solids Detection  
Models: MCU200

## Principles of Operation

Ultrasonic technology can be used to discriminate between immiscible liquids to indicate an interface or to detect suspended solids. It is helpful to understand the operating principles in order to select the most suitable sensor.

### Sludge detection (sensors 433SD and 442SD)

Solids suspended in a liquid will scatter ultrasonic beams causing attenuation. This attenuation depends on the size and nature of the particles.

For typical sewage sludges, the ultrasonic sensors can detect 1% to 30% suspended solids within a slurry. Industrial slurries such as fine pottery slips can often be measured up to 65% solids by weight.

The 433SD sensor is normally suspended in a settlement tank or separator.



The 422SD sensor pair is typically installed across a pipe.

### Interface detection (sensor 402SD)

For interface detection between two immiscible liquids, two techniques are available: *ultrasonics attenuation* and *ultrasonic refraction*.


Ultrasonic attenuation is the reduction in signal energy as it is transmitted through the liquid. Viscous liquids, emulsions and liquids with entrained solids generally have a higher ultrasonic attenuation than low viscosity clear liquids such as water. When the attenuation difference is sufficient, the amplifier gain can be adjusted so that the ultrasonic signal passes through the less attenuative liquid but is stopped by the more attenuative liquid.

The refraction technique is used to detect the interface where two immiscible liquids have similar attenuations. When the sensor is oriented at an angle of 10 degrees from horizontal, and the interface level is within the gap of the sensor, a small signal is received. The gain of the MCU200 control unit can be set to activate the relay when little signal is received.




### INTERFACE DETECTION BY ATTENUATION



**Sensor in oil:**  
The ultrasonic beam is attenuated and will not reach the receiver crystal



**Sensor in water:**  
The ultrasonic beam reaches the receiver crystal




### INTERFACE DETECTION BY REFRACTION



Suspended Solids Detection  
Models: MCU200

## Principles of Operation



## MCU Control Unit

TABLE 1

Base Model	<b>Code</b>
Interface sensor	MCU200

TABLE 2


Power Supply	<b>Code</b>
MCU control unit. For use with all sensors. 220/110Vac (50/60 Hz). Safe area only.	1
MCU control unit. For use with all sensors. 24Vdc.	3

## All Ultrasonic Sensors

- All sensors can be used with the MCU200 series of controllers.
- Cables are terminated with crimped ferules to connect within the MCU200 series controller
- Ultrasonic sensors should not be used in liquids with high aeration of foam which will attenuate the signal

## 433SD Tank Mount Sensors

433SD tank mount sensors are commonly mounted within a settlement tank from above, to detect a rising sludge blanket level




**Gap Size Selection**

Sensor Gap Size	Primary Sludge at 1MHz	Primary Sludge at 3.7MHz	Secondary Sludge at 3.7MHz
100 mm (4 inch)	3 to 29%	1 to 6%	2 to 15%
150 mm (6 inch)	2 to 19%	1 to 4%	1 to 10%
200 mm (8 inch)	2 to 14.5%	0.5 to 3%	1 to 7.5%
300 mm (12 inch)	1 to 10%	0.5 to 2%	0.5 to 5%
450 mm (18 inch)	N/A	0.5 to 1.3%	0.5 to 3.3%


Note: These % solids ranges are based on typical attenuation factors for municipal waste-water sludge. Within the UK's waste-water industry, experience has found a 6 inch gap sensor at 1 MHz is suitable for a majority of Primary Sludge applications, and an 18 inch gap sensor at 3.7 MHz is suitable for a majority of Secondary Sludge applications.

**How to order tank mount sensors**


All tank mount sensors begin 433SD, then select the gap width and the cable length.




**Tank mount sensors**

TABLE 1 

Sensor Type	Code
Tank mount sensor for MCU200 series	433SD

TABLE 2 

Gap Size	Code
100mm (4 inch) tank mount gap sensor. 1 MHz / 3.7 MHz.	801M1
150mm (6 inch) tank mount gap sensor. 1 MHz / 3.7 MHz	805M1
200mm (8 inch) tank mount gap sensor. 1 MHz / 3.7 MHz.	802M1
300mm (12 inch) tank mount gap sensor. 1 MHz / 3.7 MHz.	803M1
450mm (18 inch) tank mount gap sensor. 3.7 MHz only.	804M3

TABLE 3 

Cable Length	Code
Cable length 10 meters	M10
Cable length 20 meters	M20
Customer defined cable length up to a maximum of 30m (may incur a longer lead time and additional cost)	MXX

Note: the MCU200 controller can be set to operate at either 1 MHz or 3.7 MHz. The standard frequency is 3.7 MHz, but

**402SD interface sensors**

402SD interface sensors are typically positioned either horizontally or at a 10 degree angle to detect a liquid interface.



**442SD pipe mount sensors**


442SD pipe mount sensors may be mounted across a pipe of from 100mm (4") to 300mm (12") diameter.



**How to order interface and pipe mount sensors**

**Sensor Type**  
Table 1

**Cable Length**  
Table 2



**Interface and pipe mount sensors**



Sensor Type	Code
Interface sensor. 3.7 MHz only.	402SD80
Pipe mount sensor. 1 MHz / 3.7 MHz.	442SD80



Gap Size	Code
Cable length 3 meters	M03
Cable length 6 meters	M06
Customer defined cable length up to a maximum of 30m (may incur a longer lead time and additional cost)	MXX

## Technical Specification

MCU200 Series Controller	MCU201		MCU203
Power supply	110/220 Vac or 220/240 Vac selectable		24Vdc grounded (earthed) negative
Power consumption	6VA		2.4W
Number of sensor inputs	One		
Relay output	Double-Pole Changeover (DPDT)		
	Energised when sensor is wet or dry (configurable)		
Relay rating	5A at 230V		
Enclosure size	200 x 120 x 75mm (7.9 x 4.7 x 3.0 inches)		
Enclosure rating	IP65 Polycarbonate		
Holes for glands	3 off 16mm (0.63 inches)		
Fixing centers for wall mount	188 x 88mm W x H (7.4 x 3.4 inches)		
Fixing hole diameter	4mm (0.16 inches)		
Frequency selection	1 MHz (higher sensitivity) or 3.7 MHz (standard) by switch		
LED indicators	Green for Normal. Red for Alarm. Amber for Fault. Visible through lid.		
	Green or Red selectable for wet or dry.		
Gain setting	Range switch and gain potentiometer to adjust for sensor and application		
Response time	Selectable delay of 0.5, 2, 8 or 30 seconds		
	Delay selectable for wet-to-dry or dry-to-wet changeover		
	50ms response in opposite direction		
Sensor cable check	Selectable to monitor coax screen for continuity		
	Fault condition lights the fault LED and sets relay to alarm state		
Auxiliary Input	External closed circuit input latches the output relay to achieve pump control		
Ultrasonic gap Sensors	402SD80	433SD80	442SD80
Repeatability	2mm	2mm	2mm
Operating temperature	-70 to 150°C (-94 to 302°F)	-40 to 70°C (-40 to 158°F)	-70 to 150°C (-94 to 302°F)
Maximum pressure	105 bar (1523 psi)	105 bar (1523 psi)	105 bar (1523 psi)
Power consumption	< 10 mW at sensor	< 10 mW at sensor	< 10 mW at sensor
Standard frequency	3.7 MHz	1 MHz / 3.7 MHz	1 MHz / 3.7 MHz
Cable length	3m (10 ft)	10m (33 ft)	3m (10 ft)
Sensor cable entry	IP65	IP65	IP65
Sensor cable	PTFE-insulated dual coaxial with PVC sheaf. Minimum bend radius 35 mm (1.4 inches) Terminated with crimped ferules to connect within MCU200 controller terminals		
<b>Note: MCU200 series controllers and the 4**SD sensors are for non-hazardous area use only</b>			

## Approvals

### EUROPEAN DIRECTIVES



**Electromagnetic Compatibility Directive (EMC) 2014/30/EU**

Compliant to EMC directive

**Low Voltage Directive (LVD) 2014/35/EU**


Compliant to LVD directive

**Pressure Equipment Directive (PED) 2014/68/EU:**


This product is out of the scope of the PED directive

## Technical Specification

**TOP VIEW**




**BOTTOM VIEW**




**Suspended Solids Detection**  
Models: MCU200




**Dimensional drawings**



Sensor type 433SD  
 316 stainless steel  
 Duty: Sludge blanket or interface, immiscible liquids  
 Liquid type: Viscous or with solids in suspension  
 See Table 5 on page 7 for the full specification



Sensor type 402SD  
 316 stainless steel  
 Duty: Interface, immiscible liquids  
 Liquid type: Clean, viscous with solids  
 See Table 5 on page 7 for the full specification



Sensor type 442SD  
 Across Pipe  
 Duty: Pipelines  
 Liquid type: Clean or sludge density  
 See Table 5 on page 7 for the full specification

In the interest of development and improvement Delta Mobrey Ltd, reserves the right to amend, without notice, details contained in this publication. No legal liability will be accepted by Delta Mobrey Ltd for any errors, omissions or amendments.

**Delta Mobrey Limited**  
 Hudson House, Albany Park Camberley Surrey, GU16 7PL, UK.  
 T+44 (0)1252 729140 F+44 (0)1252 729168 E sales@delta-mobrey.com W www.delta-mobrey.com

